Soils Field Tester Technician KT-13 Field Density Tests of Soils, Treated Base Courses, and Water Bound Base Courses (Sand Cone Method) Revised July 2016

Two attempts may be made by the applicant. The applicant may stop themselves once and not have that count as one of the two attempts. If the applicant stops voluntarily, draw a line at that point and note that the applicant stopped themselves then restart at the top of the next attempt. Underlined items will be administered orally

Applicant:	CIT #:	
Employer:		

TEST TRIAL

		1st Test		Stopped Test		3 rd Test	
	Determine the Volume of Jar &						
	Attachment						
1.	Weigh the assembled apparatus and record.	PASS	FAIL	PASS	FAIL	PASS	FAIL.
	(6.1.1.)	17100	11110	11100	17111	17100	1111
		-					
2.	Place the apparatus up right and open the	PASS	FAIL	PASS	FAIL	PASS	FAIL
	<u>valve.</u> (6.1.2.)	}					
3.	Fill the apparatus with water until it appears	DAGG	17 4 17			D 4 G G	
	over the valve. (6.1.3.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
]					
4.	Close the valve and remove excess water.	PASS	FAIL	PASS	FAIL	PASS	FAIL
	(6.1.4)						
5.	Weigh the apparatus and water. (6.1.5)	PASS	FAIL	PASS	FAIL	PASS	FAIL
6.	Repeat the procedure described above at least						
	twice. The volume used shall be the average	PASS	FAIL	PASS	FAIL	PASS	FAIL.
	of three determinations with a maximum	11100	17112	11100		11.00	
	variation of 3 mL. (6.1.6.)						
	Determination of Bulk Density of Sand						
7.	Place the empty apparatus upright on a firm,	D 1 0 0		D 4 0 0		D 4 0 0	
	level surface; close the valve and fill the	PASS	FAIL	PASS	FAIL	PASS	FAIL
	funnel with sand. (6.2.1.)						

Soils Field Tester Technician KT-13 Field Density Tests of Soils, Treated Base Courses, and Water Bound Base Courses (Sand Cone Method) Revised July 2016

		1st Test		Stopped Test		3 rd Test	
8.	Open the valve and keeping the funnel at least half full of sand, fill the apparatus. Close the valve sharply and empty excess sand. (6.2.2.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
9.	Weigh the apparatus and sand. Determine the net weight of sand by subtracting the mass of the apparatus. (6.2.3)	PASS	FAIL	PASS	FAIL	PASS	FAIL
1	Determination of mass of sand filling the funnel						
10.	Put sand in the apparatus and obtain the mass of the apparatus and sand. (6.3.1.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
11.	Seat the inverted apparatus on a clean, level, plane surface. (6.3.2.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
12.	Open the valve and keep open until the sand stops running. (6.3.3.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
13.	Close the valve sharply. Weigh the apparatus with remaining sand and determine the loss of sand. This loss represents the mass of sand required to fill the funnel. (6.3.4.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
14.	Replace the sand removed in the funnel determination and close the valve. (6.3.5.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
15.	Determination of Density of Soil in-placePrepare the surface of the location to be testedso that it is a level plane.(6.4.1)	PASS	FAIL	PASS	FAIL	PASS	FAIL
16.	Seat the inverted apparatus on the prepared plane surface and mark the outline of the funnel. (6.4.2.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
17.	Drill or cut a test hole. Carefully save all material. (6.4.2.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
18.	Seat the apparatus in the previously marked position, open the valve, and after the sand has stopped flowing, close the valve. (6.4.3.)	PASS	FAIL	PASS	FAIL	PASS	FAIL
19.	Weigh the apparatus and remaining sand. Determine the mass of sand used in the test. (6.4.4.)	PASS	FAIL	PASS	FAIL	PASS	FAIL

Soils Field Tester Technician KT-13 Field Density Tests of Soils, Treated Base Courses, and Water Bound Base Courses (Sand Cone Method) Revised July 2016

20. Weigh the material that was removed from the test hole. (6.4.5.) PASS FAIL FAIL FAIL FAIL FAIL FAIL FAIL FAIL FAIL	·	·		1st Test		Stoppe	Stopped Test		Гest	
weigh a representative sample for moisture determination. (6.4.6.) PASS FAIL PASS FAI	20.		emoved from the	PASS	FAIL	PASS	FAIL	PASS	FAIL	
22. Determine the moisture content in accordance with KT-11, (6.4.7.) PASS FAIL	21.	weigh a representative sample for moisture		PASS	FAIL	PASS	FAIL	PASS	FAIL	
Image: Second stand sta	22.	Determine the moisture conte	nt in accordance	PASS	FAIL	PASS	FAIL	PASS	FAIL	
21. Calculate the wet density of the material removed from the hole, (6.5.2.) PASS FAIL FAIL FAIL FAIL FAIL FAIL FAIL <td>23.</td> <td colspan="2"></td> <td>PASS</td> <td>FAIL</td> <td>PASS</td> <td>FAIL</td> <td>PASS</td> <td>FAIL</td>	23.			PASS	FAIL	PASS	FAIL	PASS	FAIL	
Image: constraint of the constraint	24.	Calculate the bulk density of	sand. (6.2.4.)	PASS	FAIL	PASS	FAIL	PASS	FAIL	
material tested to the nearest 0.1 lb/ft³ (6.5.3.) FASS FAIL FASS FAIL <td< td=""><td>25.</td><td colspan="2"></td><td>PASS</td><td>FAIL</td><td>PASS</td><td>FAIL</td><td>PASS</td><td>FAIL</td></td<>	25.			PASS	FAIL	PASS	FAIL	PASS	FAIL	
Circle One1st TestStopped Test3rd TestPASSPASSPASSFAILFAILFAILWitness Examiner: (First Try)SignatureDateWitness Examiner: (Stopped Try)SignatureDateWitness Examiner: (Stopped Try)SignatureDate	26.				FAIL	PASS	FAIL	PASS	FAIL	
1st TestStopped Test3rd TestPASSPASSPASSFAILFAILFAILWitness Examiner: (First Try)SignatureDateWitness Examiner: (Stopped Try)SignatureDateWitness Examiner: (Stopped Try)SignatureDate			Overa	ll Score						
PASS PASS PASS FAIL FAIL FAIL Witness Examiner:			Circl	e One						
FAIL FAIL FAIL Witness Examiner:		1 st Test Stopped Tes			d Test 3 rd Test					
Witness Examiner:		PASS PA				PASS				
(First Try) Signature Date Witness Examiner: (Stopped Try) Signature Date Witness Examiner:		FAIL FA					FAI	Ĺ		
Witness Examiner: (Stopped Try) Signature Date Witness Examiner:	Witness Examiner:									
(Stopped Try) Signature Date Witness Examiner:		(First Try) Signature				Date				
Witness Examiner:		Witness Examiner:								
		(Stopped Try) Signature				Date				
(Re-Test) Signature Date		Witness Examiner:								
		(Re-Test) Signature				Date				

÷.: